

# TULA


performance - twoway



Arcluce Code **0472008P-830-21**

Ex Code

Code EAN **8054378321894**



## Technical information

**Light source:** LED, 3000K, CRI>80

**Indirect light source:** LED, 3000K, CRI>80

**Luminaire efficacy:** 78lm/W

**Luminaire:** 9W , 700lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz

**Wiring:** PC

**Optics:** elliptic 22°x41°

**Indirect Optic:** elliptic 22°x41°

**Color:** Aluminium - 21

**Weight:** 0.82 kg

**Size:**  
A: Ø 50mm  
B: 121mm  
C: 131mm







0,02m<sup>2</sup>



## Appliance

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Transparent microprismatic visible screen, internal screen in PMMA.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Wall mounted.
- Waterproof grommet for single cable entry.
- Die-cast aluminium base plate (EN 47100).

## Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



# TULA

performance - twoway

Arcluce Code **0472008P-830-21**

Ex Code

Code EAN **8054378321894**



## Specifications

Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Transparent microprismatic visible screen, internal screen in PMMA. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K, 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 78lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Wall mounted. Waterproof grommet for single cable entry. Die-cast aluminium base plate (EN 47100).

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. TULA