

PANTHEON2


pantheon2



Arcluce Code **0681007A-840-21**

Ex Code

Code EAN **8054378328879**



Technical information

Light source: LED, 4000K, CRI>80

Luminaire efficacy: 100lm/W

Luminaire: 79W , 7900lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: wide flood 42°

Color: Aluminium - 21

Weight: 9.7 kg

Size:
A: Ø 316mm
B: 418mm
C: 425mm

CE

IP67

IK08



0,09m²



Appliance

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Wiring on removable galvanized steel tray.
- Driver protected against voltage surges.
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 5mm thermal-shock resistant tempered glass.
- Goniometer scale to aim light.

Installation

- Galvanized and painted steel bracket.
- Aiming possibility.
- Double grommet M20 for through wiring.

Note

- These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Norm

- It complies with standards EN 60598-1 and EN 60598-2-5.

PANTHEON2

pantheon2



Arcluce Code **0681007A-840-21**

Ex Code

Code EAN **8054378328879**



Specifications

Die-cast aluminium body and trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. Reflector made of engineering plastic metalized in high-vacuum. Screen made of 5mm thermal-shock resistant tempered glass. Goniometer scale to aim light.

It complies with standards EN 60598-1 and EN 60598-2-5.

LED sources available in color temperatures 4000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 100lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Galvanized and painted steel bracket. Aiming possibility. Double grommet M20 for through wiring.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Brand ARCLUCE mod. PANTHEON2